






































Photo	Specification	Model	end user price
<b>HD-TVI Camera 1 Megapixel (720P)</b>			
	<b>HD -TVI Dome</b> camera 1Megapixel HD720p @25fps, 1/3" CMOS Image sensor, 2.8mm Lens, 20m IR, IR cut filter with auto switch, Indoor dome, ICR, 0.01 Lux/F1.2, Wide operating temperature range (-40°~60°) IP66, 12 VDC	DS-2CE56C0T-IRPF	1,390.00
	<b>HD -TVI Dome</b> camera 1.3 Megapixel HD720p @25fps, 1/3" CMOS Image sensor, 2.8mm Lens, 20m IR, IR cut filter with auto switch, Indoor dome, ICR, 0.01 Lux/F1.2, Wide operating temperature range (-40°~60°) IP66, 12 VDC	DS-2CE56C2T-IR	1,490.00
	<b>HD -TVI Dome</b> camera 1Megapixel HD720p @25fps, 1/3" CMOS Image sensor, 3.6mm Lens, DNR, 40m IR, Exir tehnology, ICR, 0.01 Lux/F1.2, Wide operating temperature range (-40°~60°) IP66, 12 VDC	DS-2CE56C0T-IT3	2,480.00
	<b>HD -TVI Bullet</b> camera 1Megapixel HD720p @25fps, 1/3" CMOS Image sensor, 2.8mm Lens, 20m IR, IR cut filter with auto switch, Outdoor Bullet, ICR, 0.01 Lux/F1.2, Wide operating temperature range (-40°~60°) IP66, 12 VDC	DS-2CE16C0T-IRP/IRPF	1,460.00
	<b>HD -TVI Bullet</b> camera 1Megapixel HD720p @25fps, 1/3" CMOS Image sensor, 3.6mm Lens, DNR, 80m IR, Exir tehnology, Outdoor bullet, ICR, 0.01 Lux/F1.2, Wide operating temperature range (-40°~60°) IP66 weatherproof, 12 VDC	DS-2CE16C0T-IT5	2,850.00
<b>HD-TVI Camera 2 Megapixel (Full HD 1080p)</b>			
	<b>HD -TVI Dome</b> camera 2Megapixel HD1080p @25fps, 1/3" CMOS Image sensor, 3.6mm Lens, 20m IR, IR cut filter with auto switch, Indoor dome, ICR, 0.01 Lux/F1.2, Wide operating temperature range (-40°~60°) IP66, 12 VDC	DS-2CE56D0T-IRPF	2,050.00
	<b>HD -TVI Dome</b> camera 2Megapixel HD1080p @25fps, 1/3" CMOS Image sensor, 3.6mm Lens, 20m IR, IR cut filter with auto switch, Outdoor dome, ICR, 0.01 Lux/F1.2, Wide operating temperature range (-40°~60°) IP66, 12 VDC	DS-2CE56D0T-IRM	2,410.00
	<b>HD -TVI Dome</b> camera 2 Megapixel HD1080p @25fps, 1/3" CMOS Image sensor, Outdoor IR Vari-focal 2.8~12mm Lens, 40m IR, IR cut filter with auto switch, ICR, 0.01 Lux/F1.2, DWDR, Wide operating temperature range (-40°~60°) IP66, 12 VDC	DS-2CE56D1T-VFIR3	4,840.00

	<b>HD -TVI Bullet</b> camera 2 Megapixel HD1080p @25fps, 1/3" CMOS Image sensor, 3.6mm Lens, 20m IR, IR cut filter with auto switch, Outdoor Bullet, ICR, 0.01 Lux/F1.2, Wide operating temperature range (-40°~60°) IP66, 12 VDC	DS-2CE16D0T-IRPF	2,120.00
	<b>HD -TVI Bullet</b> camera 2 Megapixel HD1080p @25fps, 1/3" CMOS Image sensor, 3.6mm Lens, DNR, 20m IR, Exir tehnology, Outdoor bullet, ICR, 0.01 Lux/F1.2, Wide operating temperature range (-40°~60°) IP66 weatherproof, 12 VDC	DS-2CE16D0T-IT1	2,880.00
	<b>HD -TVI Bullet</b> camera 2 Megapixel HD1080p @25fps, 1/3" CMOS Image sensor, 3.6mm Lens, DNR, 40m IR, Exir tehnology, Outdoor bullet, ICR, 0.01 Lux/F1.2, Wide operating temperature range (-40°~60°) IP66 weatherproof, 12 VDC	DS-2CE16D0T-IT3	3,290.00
	<b>HD -TVI Bullet</b> camera 2 Megapixel HD1080p @25fps, 1/3" CMOS Image sensor, 3.6mm Lens, DNR, 80m IR, Exir tehnology, Outdoor bullet, ICR, 0.01 Lux/F1.2, Wide operating temperature range (-40°~60°) IP66 weatherproof, 12 VDC	DS-2CE16D0T-IT5	3,660.00
	<b>HD -TVI Bullet</b> camera 2 Megapixel HD1080p @25fps, 1/2.7" CMOS Image sensor, 2.8~12mm Vari-focal Lens, DNR, 40m IR, Exir tehnology, Outdoor bullet, ICR, 0.01 Lux/F1.2, Wide operating temperature range (-40°~60°) IP66 weatherproof, 12 VDC	DS-2CE16DOT-VFIR3F	4,820.00
<b>HD-TVI Camera 2 Megapixel (Full HD 1080p) D8T Startlight</b>			
	<b>HD -TVI Bullet</b> camera 2 Megapixel HD1080p @25fps, 1/3" CMOS Image sensor, 3.6mm Lens, DNR, 40m IR, Exir tehnology, Outdoor bullet, ICR, 0.01 Lux/F1.2, Wide operating temperature range (-40°~60°) IP66 weatherproof, 12 VDC	DS-2CE16D8T-IT	3,730.00
	<b>HD -TVI Bullet</b> camera 2 Megapixel HD1080p @25fps, 1/3" CMOS Image sensor, 3.6mm Lens, DNR, 80m IR, Exir tehnology, Outdoor bullet, ICR, 0.01 Lux/F1.2, Wide operating temperature range (-40°~60°) IP66 weatherproof, 12 VDC	DS-2CE16D8T-IT3	4,460.00
	<b>HD -TVI Bullet</b> camera 2 Megapixel HD1080p @25fps, 1/3" CMOS Image sensor, 3.6mm Lens, DNR, 80m IR, Exir tehnology, Outdoor bullet, ICR, 0.01 Lux/F1.2, Wide operating temperature range (-40°~60°) IP66 weatherproof, 12 VDC	DS-2CE16D8T-AIT3Z	8,190.00
<b>HD-TVI Camera 3 Megapixel (1920x 1536)</b>			
	<b>HD -TVI Dome</b> camera 3 Megapixel 1920x1536 @18fps, CMOS Image sensor, 3.6mm Lens, 20m IR, Exir tehnology, DNR , ICR, 0.01 Lux/F1.2, Outdoor dome, Wide operating temperature range (-40°~60°) IP66, 12 VDC	DS-2CE56F1T-ITM	3,520.00
	<b>HD -TVI Dome</b> camera 3 Megapixel 1920x1536 @18fps, CMOS Image sensor, 3.6mm Lens, 20m IR, Exir tehnology, DNR , 120db WDR, ICR, 0.01 Lux/F1.2, Outdoor dome, Wide operating temperature range (-40°~60°) IP66, 12 VDC	DS-2CE56F7T-ITM	4,620.00
	<b>HD -TVI Bullet</b> camera 3 Megapixel 1920x1536 @18fps, 1/3" CMOS Image sensor, 3.6mm Lens, DNR, 40m IR, Exir tehnology, Outdoor bullet, ICR, 0.01 Lux/F1.2, Wide operating temperature range (-40°~60°) IP66 weatherproof, 12 VDC	DS-2CE16F1T-IT	3,520.00
	<b>HD -TVI Bullet</b> camera 3 Megapixel 1920x1536 @18fps, 1/3" CMOS Image sensor, 3.6mm Lens, DNR, 40m IR, Exir tehnology, Outdoor bullet, ICR, 0.01 Lux/F1.2, Wide operating temperature range (-40°~60°) IP66 weatherproof, 12 VDC	DS-2CE16F1T-IT3	3,950.00
	<b>HD -TVI Bullet</b> camera 3 Megapixel 1920x1536 @18fps, 1/3" CMOS Image sensor, 3.6mm Lens, DNR, 80m IR, Exir tehnology, Outdoor bullet, ICR, 0.01 Lux/F1.2, Wide operating temperature range (-40°~60°) IP66 weatherproof, 12 VDC	DS-2CE16F1T-IT5	4,470.00

	<b>HD -TVI Bullet camera 3 Megapixel</b> 1920x1536 @18fps, 1/3" CMOS Image sensor, 3.6mm Lens, DNR, 20m IR, 120db WDR, Exir tehnology, Outdoor bullet, ICR, 0.01 Lux/F1.2, Wide operating temperature range (-40°~60°) IP66 weatherproof, 12 VDC	DS-2CE16F7T-IT	4,620.00
<b>HD-TVI Camera 5 Megapixel (2592x 1944)</b>			
	<b>HD -TVI Dome camera 5 Megapixel</b> 2592x1944 @20fps, CMOS Image sensor, 3.6mm Lens, 20m IR, Exir tehnology, DNR ,BLC/AGC, ICR, 0.01 Lux/F1.2, Outdoor dome, Wide operating temperature range (-40°~60°) IP67, 12 VDC	DS-2CE56H1T-ITM	4,090.00
	<b>HD -TVI Dome camera 5 Megapixel</b> 2592x1944 @20fps, CMOS Image sensor, 3.6mm Lens, 20m IR, Exir tehnology, DNR ,BLC/AGC, ICR, 0.01 Lux/F1.2, Outdoor dome, Wide operating temperature range (-40°~60°) IP67, 12 VDC	DS-2CE56H5T-ITM	5,630.00
	<b>HD -TVI Bullet camera 5 Megapixel</b> 2592x1944 @20fps, CMOS Image sensor, 3.6mm Lens, 20m IR, Exir tehnology, DNR , BLC/AGC,Outdoor bullet, ICR, 0.01 Lux/F1.2, Wide operating temperature range (-40°~60°) IP67 weatherproof, 12 VDC	DS-2CE16H1T-IT1	5,120.00
	<b>HD -TVI Bullet camera 5 Megapixel</b> 2592x1944 @20fps, CMOS Image sensor, 3.6mm Lens, 20m IR, Exir tehnology, DNR , BLC/AGC,Outdoor bullet, ICR, 0.01 Lux/F1.2, Wide operating temperature range (-40°~60°) IP67 weatherproof, 12 VDC	DS-2CE16H5T-IT	5,630.00
	<b>HD -TVI Bullet camera 5 Megapixel</b> 2592x1944 @20fps, CMOS Image sensor, 3.6mm Lens, 40m IR, Exir tehnology, DNR , BLC/AGC,Outdoor bullet, ICR, 0.01 Lux/F1.2, Wide operating temperature range (-40°~60°) IP67 weatherproof, 12 VDC	DS-2CE16H1T-IT3	5,780.00
	<b>HD -TVI Bullet camera 5 Megapixel</b> 2592x1944 @20fps, CMOS Image sensor, 3.6mm Lens, 40m IR, Exir tehnology, DNR , BLC/AGC,Outdoor bullet, ICR, 0.01 Lux/F1.2, Wide operating temperature range (-40°~60°) IP67 weatherproof, 12 VDC	DS-2CE16H5T-IT3	6,360.00
	<b>HD -TVI Bullet camera 5 Megapixel</b> 2592x1944 @20fps, CMOS Image sensor, 3.6mm Lens, 80m IR, Exir tehnology, DNR , BLC/AGC,Outdoor bullet, ICR, 0.01 Lux/F1.2, Wide operating temperature range (-40°~60°) IP67 weatherproof, 12 VDC	DS-2CE16H1T-IT5	6,030.00
<b>Turbo HD TVI PTZ Camera</b>			
	<b>HD -TVI PTZ Camera 2 MP</b> 1/3" CMOS, 1920x1080:30fps, 3D DNR, ICR, Color: 0.05lux/F1.4, B/W:0.005lux/F1.4, Optical Zoom:23x, Focus:4.0-92mm, Digital Zoom:16X, Pan range:360° endless; Tilt range: -5°~90°(Auto Flip), Pan Speed: 0.1° -160°/s, Tilt Speed: 0.1° -120°/s, Up the Coax	DS-5223TI-A	46,900.00
	<b>HD -TVI PTZ Camera 2 MP</b> 1/2.8" CMOS, 1920x1080:30fps, 3D DNR, ICR, Color: 0.2lux/F1.6, B/W:0.02lux/F1.6, Optical Zoom:30x, Focus:4-120mm, Digital Zoom:16X, Pan Speed: 0.1° -160°/s, Tilt Speed: 0.1° -120°/s, 120m IR distance, Up the Coax	DS-2AE7230TI-A	54,990.00
	Bracket Aluminum alloy 97×182×305mm	DS-1602ZJ	1,750.00
	<b>Longse analog</b> 1/3" color CCD high resolution 700 TVL Sony Effio DSP, BOX, high quality picture,low illumination,autowhite balans,DWDR, ATR, DNR	LBCKSHE	3,490.00





	<b>Avtech analog 1/3" High Resolution Color Super HAD CCD, 700TV SONY Effio DSP, High sensitivity, Excellent image quality, ATW, ACG Auto, AES, 12Vdc, IP67 standard approved case, BUILD MICROPHON</b>	AVC412ZAP/NL-S	4,050.00
<b>Turbo HD DVR support 1 megapixel 720P</b>			
	4- ch Turbo HD/AHD/Analog interface input, Support 4 HD-TVI/AHD/CVI and analog camera with adaptive access, H.264 ,H.264+& Dual-stream video compression, Resolution 1MP 720p(1280x720) 100 fps for all chanel 4-ch video & 1-ch audio input, 1 SATA HDD interface,2x USB port, video out HDMI/VGA, 100Mbit LAN, mini 1U case, 12 VDC	DS-7104HGHI-F1	4,970.00
	8- ch Turbo HD/AHD/Analog interface input, Support 8 HD-TVI/AHD/CVI and analog camera with adaptive access, H.264 ,H.264+& Dual-stream video compression, Resolution 1MP 720p(1280x720) 200 fps for all chanel, 4-ch video & 1-ch audio input, 1 SATA HDD interface,2x USB port, video out HDMI/VGA, 100Mbit LAN mini 1U case, 12 VDC	DS-7108HGHI-F1	7,680.00
	16-ch Turbo HD/AHD/Analog interface input, Support 16 HD-TVI/AHD/CVI and analog camera with adaptive access, H.264 ,H.264+& Dual-stream video compression, Resolution 1MP 720p(1280x720) 400 fps for all chanel, 16 video & 1-ch audio input, 1 SATA HDD interface,2x USB port, video out HDMI/VGA , 100Mbit LAN, mini 1U case, 12 VDC	DS-7116HGHI-F1	11,700.00
<b>Turbo HD DVR support 2 megapixel full hd 1080p Turbo HD 4.0</b>			
	4- ch Turbo HD/AHD/Analog interface input, Support 4 HD-TVI/AHD/CVI and analog camera with adaptive access, H.264 ,H.264+& Dual-stream video compression, Resolution 2MP 1080p(1920x1080) 40 fps@1080, 100 fps@720p for all chanel 4-ch video &1-ch audio input, 1 SATA HDD 6TB max, interface,2x USB port, video out HDMI/VGA, 100Mbit LAN mini 1U case, 12 VDC	DS-7104HQHI-F1/N DVR Turbo HD 4.0	6,290.00
	8- ch Turbo HD/AHD/Analog interface input, Support 8 HD-TVI/AHD/CVI and analog camera with adaptive access, H.264 ,H.264+& Dual-stream video compression, Resolution 2MP 1080p(1920x1080) 80 fps@1080, 200 fps@720p for all chanel 8-ch video &1-ch audio input, 1 SATA HDD 6TB max, interface,2x USB port, video out HDMI/VGA, 100Mbit LAN mini 1U case, 12 VDC	DS-7108HQHI-F1/N DVR Turbo HD 4.0	10,090.00
	16- ch Turbo HD/AHD/Analog interface input, Support 16 HD-TVI/AHD/CVI and analog camera with adaptive access, H.264 ,H.264+& Dual-stream video compression, Resolution 2MP 1080p(1920x1080) 160 fps@1080, 400 fps@720p for all chanel 16-ch video &1-ch audio input, 1 SATA HDD 6TB max, interface, 2x USB port, video out HDMI/VGA, 100Mbit LAN mini 1U case. 12 VDC	DS-7116HQHI-F1/N DVR Turbo HD 4.0	16,000.00
	4- ch Turbo HD/AHD/Analog interface input, Support 4 HD-TVI/AHD/CVI or analog camera + 1 IP camera up to 2MP, H.264 ,H.264+& Dual-stream video compression, Resolution up to 3MP (1920x1536) for chanel 1, to 2 MP (1920x1080) for chanel 2-4 TVi/AHD/CVI, 48 fps@3MP/1080P, 100 fps@720p for all chanel 4-ch video &1-ch audio input, 1 SATA HDD 6TB max, interface,2x USB port, video out HDMI/VGA/BNC, 100Mbit LAN 12 VDC	DS-7204HQHI-K1 Turbo HD 4.0 Pentabrid H.265+	7,530.00
	8- ch Turbo HD/AHD/Analog interface input, Support 8 HD-TVI/AHD/CVI or analog camera + 2 IP camera up to 2MP, H.264 ,H.264+& Dual-stream video compression, Resolution up to 3MP (1920x1536) for chanel 1-2, to 2 MP (1920x1080) for chanel 3-8 TVi/AHD/CVI, 96 fps@3MP/1080P, 200 fps@720p for all chanel 4-ch video &1-ch audio input, 1 SATA HDD 6TB max, interface,2x USB port, video out HDMI/VGA/BNC, 100Mbit LAN 12 VDC	DS-7208HQHI-K1 Turbo HD 4.0 Pentabrid H.265+	11,100.00
	16- ch Turbo HD/AHD/Analog interface input, Support 8 HD-TVI/AHD/CVI or analog camera + 2 IP camera up to 2MP, H.264 ,H.264+& Dual-stream video compression, Resolution up to 3MP (1920x1536) for chanel 1-4, to 2 MP (1920x1080) for chanel 5-16 TVi/AHD/CVI, 192 fps@3MP/1080P, 400fps@720p for all chanel 4-ch video &1-ch audio input, 1 SATA HDD 6TB max, interface,2x USB port, video out HDMI/VGA/BNC, 100Mbit LAN 12 VDC	DS-7216HQHI-K1 Turbo HD 4.0 Pentabrid H.265+	19,200.00

	16- ch Turbo HD/AHD/Analog interface input, Support 8 HD-TVI/AHD/CVI or analog camera + 2 IP camera up to 2MP, H.264 ,H.264+& Dual-stream video compression, Resolution up to 3MP (1920x1536) for chanel 1-4, to 2 MP (1920x1080) for chanel 5-16 TVI/AHD/CVI, 192 fps@3MP/1080P, 400fps@720p for all chanel 4-ch video &1-ch audio input, 1 SATA HDD 6TB max, interface,2x USB port, video out HDMI/VGA/BNC, 100Mbit LAN 12 VDC	DS-7216HQHI-K2 Turbo HD 4.0 Pentabrid H.265+	20,700.00
<b>Turbo HD DVR support 5 megapixel (2592x1944) DVR Turbo HD 4.0</b>			
	4- ch Turbo HD/AHD/Analog interface input, Support 4 HD-TVI/AHD/CVI or analog camera + 2IP camera up to 5MP, H.264 ,H.264+& Dual-stream video compression, Resolution up to 5MP (2592x1944) for TVI/1080P, 40fps @5MP, 60fps @3MP, 100 fps@1080p/720p/960H, 4-ch video &1-ch audio input, 4 alarm input 1 output, 1 SATA HDD 6TB max, interface,2x USB port, video out HDMI/VGA/BNC, 100Mbit LAN 12 VDC	DS-7204HUHI-K1 Turbo HD 4.0 Pentabrid H.265+	10,700.00
	8- ch Turbo HD/AHD/Analog interface input, Support 8HD-TVI/AHD/CVI or analog camera + 2IP camera up to 5MP, H.264 ,H.264+& Dual-stream video compression, Resolution up to 5MP (2592x1944) for TVI/1080P, 80fps @5MP, 120fps @3MP, 200 fps@1080p/720p/960H, 8-ch video &1-ch audio input, 4 alarm input 1 output, 1 SATA HDD 6TB max, interface,2x USB port, video out HDMI/VGA/BNC, 100Mbit LAN 12 VDC	DS-7208HUHI-K1 Turbo HD 4.0 Pentabrid H.265+	17,400.00
	16- ch Turbo HD/AHD/Analog interface input, Support 16HD-TVI/AHD/CVI or analog camera + 2IP camera up to 5MP, H.264 ,H.264+& Dual-stream video compression, Resolution up to 5MP (2592x1944) for TVI/1080P, 160fps @5MP, 240fps @3MP, 400 fps@1080p/720p/960H, 16-ch video &1-ch audio input, 4 alarm input 1 output, 2 SATA HDD 6TB max, interface,2x USB port, video out HDMI/VGA/BNC, 100Mbit LAN 12 VDC	DS-7216HUHI-K2 Turbo HD 4.0 Pentabrid H.265+	31,900.00
<b>Hard disk drive for video survillence</b>			
	<b>TOSHIBA 1TB 64MB SATA III 7.200 rpm</b>	DT01ACA100	4,270.00
	<b>TOSHIBA 2TB 64MB SATA III 7.200 rpm</b>	DT01ACA200	6,260.00
	<b>WD 1TB 3.5" 64MB PURPLE SURVEILLANCE</b>	WD10PURX	4,690.00
	<b>WD 2TB 3.5" 64MB PURPLE SURVEILLANCE</b>	WD20PURX	6,570.00
	<b>WD 3TB 3.5" 64MB PURPLE SURVEILLANCE</b>	WD30PURX	9,650.00
	<b>WD 4TB 3.5" 64MB PURPLE SURVEILLANCE</b>	WD40PURX	11,310.00
<b>IP Camera (ONVIF compatible) 2 Megapixel Full HD 1080p</b>			
	IP Bullet camera 1.3MP Image Sensor: 1/3" Progressive Scan CMOS, Min. Illumination: 0.01 lux@F1.2, AGC on, 0.02 lux@F1.8,AGC on Shutter time: 1/25s ~1/100,000s, 6 mm @F2.15, Lens Mount: M12, Day& Night: Electronic, Max. Image Resolution: 1280x960, F. ate:50Hz:25fps(1280x960),25fps(1280x720),SD Card max 32GB, 85.5 × 83 × 165 mm	DS-2CD864-EI3	12,023.00
	Mount: Indoor/Outdoor wall mount, Feature: Suitable for box camera, indoor/outdoor housing, Construction:Aluminum alloy, Weight:765g(1.69lbs) Dimension: 304x71x100mm(11.79"x2.80"x3.94"), For HikVision DS-2CD864-EI3	DS-1213ZJ	990.00
	<b>IP Dome camera 2MP, 1/2.8" Progressive CMOS,1920x1080:25fps(P)/30fps(N), 4.0mm/F2.0 lens, ICR,IR range: up to 30m, 0lux with IR, H.264/MJPEG, dual-stream, IP66, DC12V &amp; PoE, DWDR, 3D DNR, BLC, (IP66), 12 VDC</b>	DS-2CD2120F-I	6,580.00









	<b>IP Bullet</b> camera 2MP, 1/2.8" Progressive CMOS,1920x1080:25fps(P)/30fps(N), 4.0mm/F2.0 lens, ICR,IR range: up to 30m, Olux with IR, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, (IP66), 12 VDC	DS-2CD1021F-I	5,970.00
	<b>IP Bullet</b> 1/2.8" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Powered by Darkfighter technology,Color: 0.005 lux @(F1.2, AGC ON), 0 lux with IR; 25fps/30fps(1920x1080); 4mm lens optional; 120dB WDR; VCA functions; 3 streams; 3D DNR; BLC; ICR; EXIR 2.0; All-metal housing, IP67; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; Hik-Connect cloud service up to 50m IR distance.*FHWD model: 50fps/60fps(1920x1080)	DS-2CD2T25FHWD-I5	10,300.00
<b>IP Camera (ONVIF compatible) 4 Megapixel EasyIP 2.0 (H.264+)</b>			
	<b>IP Dome</b> 1/3" Progressive CMOS, ICR, 2688x1520:20fps, 2.8mm/F2.0 lens (4/6mm optional), H.264+&H.264, IP67,IK10, DWDR, 3D DNR, BLC, IR range: up to 30m, DC12V & PoE,Support mobile monitoring via Hik-Connect or iVMS-4500 *power supply no included	DS-2CD1141	7,830.00
	<b>IP Dome</b> camera 4MP,1/3" Progressive CMOS, ICR, 0lux with IR, 2688x1520: 20fps, 4mm/F2.0 lens 2.812mm , H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, Support on-board storage up to 64GB (SD card not included), 3-axis adjustment, IR range: up to 30m, Vandal-proof housing, Support Mobile Monitoring via EZVIZ P2P, H.264+ Optimized Codec	DS-2CD2142FWD-I	8,880.00
	<b>IP Dome</b> camera 4MP,1/3" Progressive CMOS, ICR, 0lux with IR, 2688x1520: 20fps, 4mm/F2.0 lens 2.812mm , H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, Support on-board storage up to 64GB (SD card not included), 3-axis adjustment, IR range: up to 30m, Vandal-proof housing, Support Mobile Monitoring via EZVIZ P2P, H.264+ Optimized Codec, W: Built-in Wi-Fi	DS-2CD2142FWD-IW	9,950.00
	<b>IP Dome</b> 1/3" Progressive CMOS, ICR, 2688x1520:20fps, <b>2.8~12mm VF lens</b> , H.264+&H.264, IP67,IK10, 120db WDR, 3D DNR, BLC, IR range: up to 30m, DC12V & PoE, TF card slot, Support mobile monitoring via Hik-Connect or iVMS-4500 *power supply no included -IZ: motorized vari-focal lens	DS-2CD1741FWD-IZ	15,250.00
	<b>IP Bullet</b> 1/3" Progressive CMOS, ICR, 2688x1520:20fps, 2.8mm/F2.0 lens (4/6mm optional), H.264+&H.264, IP67, DWDR, 3D DNR, BLC, IR range: up to 30m, DC12V & PoE,Support mobile monitoring via Hik-Connect or iVMS-4500 *power supply no included	DS-2CD1041	7,690.00
	<b>IP Bullet</b> 1/3" Progressive CMOS, ICR, 2688x1520:20fps, <b>2.8~12mm VF lens</b> , H.264+&H.264, IP67, 120db WDR, 3D DNR, BLC, IR range: up to 30m, DC12V & PoE, TF card slot, Support mobile monitoring via Hik-Connect or iVMS-4500 *power supply no included -IZ: motorized vari-focal lens	DS-2CD1641FWD-IZ	15,250.00
<b>IP Camera (ONVIF compatible) 5 Megapixel EasyIP 3.0 (H.265+)</b>			
	<b>IP Dome</b> 1/2.5" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.01 lux@(F1.2, AGC ON), 0 lux with IR; 20fps(2560x1920), 25fps/30fps(2560x1440, 2048x1536, 1920x1080); 2.8mm lens optional; 120dB WDR; VCA functions; 3 streams; 3D DNR; BLC; ICR; EXIR 2.0, up to 30m; All-metal housing, IP67, IK10; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; Hik-Connect cloud service	DS-2CD2155FWD-I EasyIP 3.0 (H.265+)	10,400.00
	<b>IP Dome</b> 1/2.5" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.01 lux@(F1.2, AGC ON), 0 lux with IR; 20fps(2560x1920), 25fps/30fps(2560x1440, 2048x1536, 1920x1080); 2.8mm lens optional; 120dB WDR; VCA functions; 3 streams; 3D DNR; BLC; ICR; EXIR 2.0, up to 30m; All-metal housing, IP67, IK10; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; Hik-Connect cloud serviceW: Built-in Wi-Fi	DS-2CD2155FWD-IW EasyIP 3.0 (H.265+)	11,470.00

	<b>IP Bullet 1/2.5" Progressive Scan CMOS;</b> H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.01 lux@(F1.2, AGC ON), 0 lux with IR; 20fps(2560×1920), 25fps/30fps(2560×1440, 2048×1536, 1920×1080); 2.8mm lens optional; 120dB WDR; VCA functions; 3 streams; 3D DNR; BLC; ICR; EXIR 2.0, up to 30m; All-metal housing, IP67; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service	DS-2CD2055FWD-I EasyIP 3.0 (H.265+)	10,400.00
	<b>IP Bullet 1/2.5" Progressive Scan CMOS;</b> H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.01 lux@(F1.2, AGC ON), 0 lux with IR; 20fps(2560×1920), 25fps/30fps(2560×1440, 2048×1536, 1920×1080); 4mm lens optional; 120dB WDR; VCA functions; 3 streams; 3D DNR; BLC; ICR; EXIR 2.0; All-metal housing, IP67; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service, up to 50m IR distance	DS-2CD2T55FWD-I5 EasyIP 3.0 (H.265+)	12,100.00
<b>IP Camera (ONVIF compatible) 8 Megapixel EasyIP 3.0 (H.265+)</b>			
	<b>IP Dome 1/2.5" Progressive Scan CMOS;</b> H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.01 lux@(F1.2, AGC ON), 0 lux with IR; 20fps(3840×2160), 25fps/30fps (2560×1920, 2560×1440, 2048×1536,1920×1080); 2.8mm lens optional; 120dB WDR; VCA functions; 3 streams; 3D DNR; BLC; ICR; EXIR 2.0, up to 30m; All-metal housing, IP67, IK10; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud	DS-2CD2185FWD-I EasyIP 3.0 (H.265+)	15,500.00
	<b>IP Bullet 1/2.5" Progressive Scan CMOS;</b> H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.01 lux@(F1.2, AGC ON), 0 lux with IR; 20fps(3840×2160), 25fps/30fps (2560×1920, 2560×1440, 2048×1536,1920×1080); 2.8mm lens optional; 120dB WDR; VCA functions; 3 streams; 3D DNR; BLC; ICR; EXIR 2.0; All-metal housing, IP67; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service	DS-2CD2T85FWD-I5 EasyIP 3.0 (H.265+)	15,900.00
	<b>IP Bullet 1/2.5" Progressive Scan CMOS;</b> H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.01 lux@(F1.2, AGC ON), 0 lux with IR; 20fps(3840×2160), 25fps/30fps (2560×1920, 2560×1440, 2048×1536,1920×1080); 2.8mm lens optional; 120dB WDR; VCA functions; 3 streams; 3D DNR; BLC; ICR; EXIR 2.0; All-metal housing, IP67; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service	DS-2CD2T85FWD-I8 EasyIP 3.0 (H.265+)	16,500.00
<b>Network video recorder NVR76 4K</b>			
	NVR 8-ch , 4K Recording Resolution 8MP/6MP/5MP/3MP/1080P, Incoming bandwidth: 80Mbps, H.265/H.264/H.264+/MPEG4,1 audio input, 1 audio output, Alarm 16input, 4 output , 2 x SATA interface Up to 6TB, 2 x USB, standalone 1U case	DS-7608NI-K2	13,990.00
	NVR 16-ch , Recording Resolution 6MP/5MP/3MP/1080P, Incoming bandwidth: 160Mbps, Outgoing bandwidth: 80Mbps, 1 audio input, 1 audio output, Alarm 4input, 4 output , 2 SATA interface Up to 4TB, 2 x USB, standalone 1U case	DS-7616NI-E2/A	13,990.00
	NVR 16-ch , 4K Recording Resolution 8MP/6MP/5MP/3MP/1080P, Incoming bandwidth: 160Mbps ,H.265/H.264/H.264+/MPEG4, 1 audio input, 1 audio output, Alarm 16input, 4 output , 2 x SATA interface Up to 6TB, 2 x USB, standalone 1U case	DS-7616NI-K2	14,500.00
	NVR 16-ch , 4K Recording Resolution 8MP/6MP/5MP/3MP/1080P, Incoming bandwidth: 160Mbps ,H.265/H.264/H.264+/MPEG4, 1 audio input, 1 audio output, Alarm 16input, 4 output ,4 x SATA interface Up to 6TB, 2 x USB, standalone 1U case, VGA, HDMI	DS-7716NI-K4	27,760.00
	NVR 32-ch , Recording Resolution 6MP/5MP/3MP/1080P, Incoming bandwidth: 200Mbps, Outgoing bandwidth: 80Mbps, 1 audio input, 1 audio output, 2 x SATA interface Up to 6TB, 2 x USB, standalone 1U case	DS-7632NI-E2	21,400.00
	NVR 32-ch , Recording Resolution 5MP/3MP/1080P, Incoming bandwidth: 160Mbps, Outgoing bandwidth: 160Mbps, 1 audio input, 0 audio output, 2 x SATA interface Up to 6TB, HDMI & VGA & CVBS video out 2 x USB, standalone 1U case	DS-7632NI-ST	26,550.00
	NVR 32-ch ,4K Recording Resolution 8MP/6MP/5MP/3MP/1080P, Incoming bandwidth: 256Mbps ,H.265/H.264/H.264+/MPEG4, 1 audio input, 1 audio output, Alarm 16input, 4 output , 4 x SATA interface Up to 6TB, 2 x USB, standalone 1U case, VGA, HDMI	DS-7732NI-K4	35,200.00
















### Network Video Recorder PoE(power over ethernet)



	NVR 4-ch with 4 poe port, Recording Resolution 6MP/5MP/3MP/1080P, Incoming bandwidth: 40Mbps, Outgoing bandwidth: 80Mbps, 4x LAN PoE, 1 audio input, 1 audio output, Alarm 4input, 4 output , 1 SATA interface Up to 4TB, 2xUSB, standalone 1U case	DS-7604NI-E1/4P/A	12,560.00
	NVR 8-ch with 8 poe port, NVR 8-ch , 4K Recording Resolution 8MP/6MP/5MP/3MP/1080P, Incoming bandwidth: 80Mbps, H.265/H.264/H.264+/MPEG4,1 audio input, 1 audio output, Alarm 16input, 4 output , 2 x SATA interface Up to 6TB, 2 x USB, standalone 1U case	DS-7608NI-K2/8P	18,900.00
	NVR 16-ch with 16poe port, Recording Resolution 6MP/5MP/3MP/1080P, Incoming bandwidth: 160Mbps, Outgoing bandwidth: 80Mbps, 16x LAN PoE, 1 audio input, 1 audio output, Alarm 4input, 1 output ,2 SATA interface Up to 6TB, 2xUSB, standalone 1U case	DS-7616NI-E2/16P/A	26,400.00
	NVR 16-ch with 16poe port, 4K Recording Resolution 8MP/6MP/5MP/3MP/1080P, Incoming bandwidth: 160Mbps ,H.265/H.264/H.264+/MPEG4, 1 audio input, 1 audio output, Alarm 16input, 4 output , 2 x SATA interface Up to 6TB, 2 x USB, standalone 1U case	DS-7616NI-K2/16P	27,200.00

### Power supply & adapters

	Multiview adapter 1 Amp	12DC 1A	290.00
	Multiview adapter 2 Amp	12DC 2A	447.00
	Multiview adapter 3 Amp	12DC 3A	545.00
	Multiview adapter 5 Amp	12DC 5A	762.00
	Multiview DC 12V   Output range 5Amp ADC power 60W   Efficiency 78% Overload protection   270 g	HS60-12	999.00
	Multiview DC 12V   Output range 10Amp DC power 120W   Efficiency 81% Overload protection   450 g	HS120-12	1,232.00
	Multiview DC 12V   Output range 15Amp DC power 180W   Efficiency 80% Overload protection   850 g	HS180-12	1,545.00
	Multiview DC 12V   Output range 20Amp DC power 250W   Efficiency 80% Overload protection   850 g	HS250-12	2,470.00
	Multiview DC 12V   Output range 30Amp DC power 360W   Efficiency 80%   Overload protection   1050 g	S-360-12	3,499.00
	Multiview Output 12VDC 9channel   Total Output 10Amp DC power 120W Efficiency 85%   Overload protectio   High voltage protectio	MPS120-A9	3,087.00



	MPS-250-20A / 18 channel Output 12VDC   Total Output 20Amp DC   power 250W Efficiency 87%   Overload protectio   High voltage protectio	MPS250-18	5,210.00
	MPS-300-18A / 18 kanaliOutput 12VDC   Total Output 25ADC   power 300W Efficiency 87%   Overload protectio   High voltage protectio	MPS300-18A	5,762.00
<b>Accessories</b>			
	Controller with 3D (Pan/Tilt,Zoom) joystick, Set or call the set points and cruise tracks, Manually or automatically control, RS-485/RS-232(PC) communication, Baud rate: 2400-19200Bps, Communication distance: Max.1200m, Dimension:95(H)X205(L)X205(W) mm	SDK55	4,630.00
	Controller with 3D (Pan/Tilt,Zoom) joystick, Set or call the set points and cruise tracks, Manually or automatically control RS-485/RS-232(PC) communication, Baud rate: 2400-19200Bps, Communication distance: Max.1200m	SDK65	8,748.00
	Weatherproof of IR Illuminator Available IR distance:130m 198pcs 8-14μ IR IED Size:200(L)*143(H)*88(W) Power: 12V DC MAX 28W Weight: 2kg	LEDi130	4,630.00
<b>Connectors &amp; Testers</b>			
	3 part BNC male conector	BNC-CRIMP	26.50
	Dc cord male 25cm	dc pin	37.00
	Dc cord female 25cm	dc pin	45.00
	MICROPHONE	RX-501C-3c	352.00
	HD-CVI/AHD/TVI 1 channel passive video balun,screw free and link	Video balun	450.00
	HD-CVI/AHD/TVI 1 LCD security monitor	43TA	11,800.00
<b>Coaxial &amp; Alarm &amp; Network cable</b>			
	LinkPro Combo (RG59 + Power), Brainding 128 Bonded AL PVC + 2x0.50mm power	combo CCA +2x0.5	27.40
	LinkPro Combo (RG59 + Power), Brainding 128 Bonded AL PVC + 2x0.75mm power	combo CCA +2x0.75	30.00
	LinkPro Alarm 6 x 0.22, shild 100m	6x0.22	15.50
	Cat5e RJ45 Crimp-On Plug Connector for Network,UTP (Twisted Pair)Cable,	RJ45	7.00

	Cat6e RJ45 Crimp-On Plug Connector for Network,UTP (Twisted Pair)Cable,	RJ45	12.80
	UTP Cat5E - 24AWG Network Cable , Conductor 0.51mm , 305m Box	UTP Cat5E	9.8/m
	FTP Cat5E - 24AWG Network Cable , Conductor 0.51mm, ALFoil, 305m Box	FTP Cat5E	13.15/m
	FTP Cat6E - 24AWG Network Cable , Conductor 0.51mm, ALFoil, 305m Box	FTP Cat6E	23.5/m

Cenite se izraženi vo denari so premetan DDV.

Cenovnikot e validen od 12.02.2018 godina.

